

THREE PHASE SOLAR GTI

RG-NT SERIES



FEATURES

- IP65 ingress protection 10+years R&D accumulation and support
- Comply with international quality standards tested by TUV,BV,Dekra etc
- Quick and easy single person installation Fault codes warning viwe on LCD display Built-in limiter optional

- Big LCD display
- Power export limit
- Compact and easy to install
- Wifi/GPRS/Lan communication optional

MODEL	RG-NT4KW	RG-NT5KW	RG-NT6KW	RG-NT8KW	RG-NT10KW
Input (DC)					
Max DC power (W)	6000	7500	9000	12000	15000
Max DC voltage (Vdc)	1000	1000	1000	1000	1000
Min working voltage (Vdc)	250	250	250	250	250
MPPT voltage range (Vdc)	250~850	250~850	250~850	250~850	250~850
Max input current / per string (A)	13/13	13/13	13/13	13/13	13/13
Number of MPP trackers	2	2	2	2	2
Strings per MPP tacker	1	1	1	1	1
AC Side / Output Parameters					
AC nominal power (W)	4000	5000	6000	8000	10000
Max AC apparent power (VA)	5000	6000	7000	8800	11000
Max output current (A)	8	10	12	15	17
Nominal AC output	50/60 Hz; 400 Vac				
AC output range	45/55 Hz; 280 ~ 490 Vac (Adj)				
Power factor	0.8leading...0.8laging				
Harmonics	< 5%				
Grid type	3 W/N/PE				
Efficiency					
Max efficiency	98.0%	98.2%	98.2%	98.3%	98.4%
Euro efficiency	97.5%	97.7%	97.7%	97.8%	97.9%
MPPT efficiency	99.9%	99.9%	99.9%	99.9%	99.9%
Safety and Protection					
DC reverse-polarity protection	yes				
DC breaker	yes				
DC/AC SPD	yes				
Leakage current protection	yes				
Insulation Impedance Detection	yes				
Residual Current protection	yes				
General Parameters					
Dimension (W/H/D)(mm)	480/400/180				
Weight (kg)	22				
Operating temperature range (°C)	-25 ~ +60				
Degree of protection	IP65				
Cooling concept	Natural convection				
Topology	Transformerless				
Display	LCD				
Humidity	0-95%, no condensation				
Communication	Standard WiFi; GPRS/LAN(optional)				
Warranty	Standard 5 years; 7/10 years optional				